

GRAB RAILS & BACK RESTS



ML330_1SS

450mm Straight Grab Rail

Specification


Material	#304 Stainless Steel - 32mmØ
Finish	Satin Stainless Steel
Dimensions	Concealed Fix - 78mmØ Mount
Specify	450mm C to C
	Please note: A indicated on the line drawings refers to the length, please see below and specify accordingly
Also Available	ML330 DESIGNER : Designer Matte Black ANMB ML330 : Antimicrobial ML327 - A= 300mm C to C ML328 - A= 350mm C to C ML329 - A= 400 mm C to C ML331 - A= 600mm C to C ML332 - A= 750mm C to C ML338 - A= 800mm C to C ML333 - A= 900mm C to C ML334 - A= 1000mm C to C ML335 - A= 1200mm C to C ML336 - A= 1500mm C to C

Note

*This unit is accessible compliant when installed in accordance with AS1428.1. guidelines.

*It is the responsibility of the installer to ensure that the surface/substrate that the unit is installed upon and the fixings used are suitable to withstand the weight bearing loads of the unit and if required as per AS1428 / Australian building code regulations.

*The materials and construction of this grab rail meet AS1428.1 force requirements to be able to withstand a force of 1100Nm applied at any position and in any direction without deformation.



A = 450mm C to C

Downloads & Resources

- Care & Maintenance
- Installation instructions
- Associated Videos
- Stainless Steel Cleaning & Maintenance

The photographs and line drawings of the products presented above are representational only.
Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.