

SHOWER SEATS & SHOWER RELATED




ML_SK107_SS

Offset Flush LH Mount Shower Grab Rail Kit

Specification

Material	ABS Plastic Chrome Plated Shower Head, Chrome 2.0m high pressure hose, brass elbow & ABS Plastic Chrome Plated Grab Rail Slider, 3 function Shower Head
Finish	Satin Stainless Steel
Mounting	Concealed Fix - 78mmØ Mount
Dimensions	Grab Rail 1100mm X 700mm, 32mm Shower Kit
Features	3 Function Shower Head: Function 1: Spray Function 2: Mist Function 3: Spray & Mist. Shower head has MAXIMUM flow rate of 6 litres per minute, kits have watermark WMKT21090, hoses are standard pressure of 150-350Kpa as per AS/NZS 3662.2006 WELS: 5 Star - 6L/min

- Notes
- * This unit is accessible compliant when installed in accordance with AS1428.1 guidelines.
 - * It is the responsibility of the installer to ensure that the surface/substrate that the unit is installed upon and the fixings used are suitable to withstand the weight bearing loads of the unit and if required as per AS1428 / Australian building code regulations.
 - * Compliant with the Force Requirements within AS1428.1: 2021, Section 14.



Downloads & Resources

[Care & Maintenance](#)
[Installation instructions](#)
[Associated Videos](#)
[Stainless Steel Cleaning & Maintenance](#)

The photographs and line drawings of the products presented above are representational only. Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.